


**Hydrogen Sulfide**  
**Filter End-of-Service Life Indicator**  
**(ESLI)**  
**(PN: 2518-2000)**



Filter is good



Replace filter

*Specifications*



### 1. Application

The Hydrogen Sulfide ESLI (PN: 2518-2000) is qualitative (yes/no) colorimetric indicator for the end-of-service life of filters. The indicator is designed to provide real-time indication of the end-of-service life of hydrogen sulfide filters.

### 2. Specifications

- |                              |  |
|------------------------------|--|
| a. Weight:                   | 5g (0.18oz)                              |
| b. Dimensions:               | 21.6mm (0.85in), $\phi$ : 25.0mm (1.0in) |
| c. Threading:                | 0.75"-20 UNEF-2A male *                  |
| d. Operating temperature:    | -20°C to 55°C (-4°F to 131°F)            |
| e. Operating humidity:       | 5% RH to 85%RH                           |
| f. Minimum detectable limit: | 1ppm•hr at 30 cm/sec face velocity       |
| g. Color change:             | Light blue to brown to black             |
| h. Storage temperature:      | 4°C to 25°C, (39°F to 77°F)              |
| i. Shelf life:               | 2 years at 4°C to 25°C, (39°F to 77°F)   |
| j. Service life:             | 2 years                                  |

\* UNEF = Unified National Imperial Screw Thread

**Cross interferences and limitations:** None known.

### 3. Operating Instructions

- Ensure that packaging pouch is intact.
- Open packaging pouch by tearing off the top part from one of side notches
- Remove ESLI from the packaging pouch.
- Remove activation plug (Figure 1).



- Hold the ESLI from the edges, as shown in Figure 2, and insert it into the ESLI housing (Figure 2).
- Screw the ESLI into the ESLI housing as shown in Figure 3.
- Replace or refill filter when the ESLI changes color Light brown or black.



Figure 1

Figure 2

Figure 3